

## Patent Abstracts of Japan

PUBLICATION NUMBER : 03122185  
PUBLICATION DATE : 24-05-91

APPLICATION DATE : 06-10-89  
APPLICATION NUMBER : 01260264

APPLICANT : THREE BOND CO LTD;

R<sup>1</sup>.S i Z ..

INVENTOR : HOSOKI SATOSHI;

INT.CL. : C09K 3/10 C08L 83/06 C08L101/00  
F16B 33/06

TITLE : SEALING MATERIAL COMPOSITION  
FOR THREADED JOINT

ABSTRACT : PURPOSE: To obtain the subject composition effective in preventing the galling of threaded joint and improving the sealability of the thread in unscrewing by compounding an  $\alpha$ ,  $\omega$ -dihydroxydiorganopolysiloxane, a specific resin powder and a crosslinking agent at specific ratios.

CONSTITUTION: The objective composition contains (A) 100 pts. wt. of an  $\alpha$ ,  $\omega$ -dihydroxydiorganopolysiloxane, (B) 5-300 pts. wt. of resin powder having a melting point of  $\leq 150^{\circ}\text{C}$  and an average particle diameter of 5-100 $\mu\text{m}$  (e.g. powder of PE, PP or nylon) and (C) 0.5-30 pts. wt. of a silane of formula (R<sup>1</sup> is univalent hydrocarbon group; Z is hydrolyzable group;  $\alpha$  is integer of 0-2) or its partially hydrolyzed and condensed product. As necessary, the composition is compounded with a filler (e.g. carbon black) or a crosslinking catalyst.

COPYRIGHT: (C)1991,JPO&Japio